



Evolution® 200



Category Benefits

- Food waste is ground into particles and flushed away in seconds
- Clean, hygienic, convenient and simple to use
- Easy method to manage food waste in the home, saving you time and helping to minimise trips to the outside dustbin
- Permanent in-house solution that is compact and sits under the sink without taking up valuable storage
- Easy to install into new or existing kitchens and can be fitted to most sinks
- Environmentally responsible, helping reduce the amount of waste that goes to landfill sites

Features

- Evolution quiet technology - 60% quieter than standard Model 45
- Evolution 3-stage grind technology
- Auto-reverse grinding action
- High-torque Dura-Drive™ induction motor
- Built-in air switch in chrome and brushed steel
- 6 Year guarantee
- Stainless steel grind elements and grind chamber
- Overload protection
- Quick Lock® mounting assembly for faster, easier installation

Sample Specification

Food waste disposer(s) shall be InSinkErator® Model Evolution 200 with 3-stage grind and quiet technologies, 1 hp (110-120V) or .75 hp (220-240V) motor, auto-reverse grind system, stainless steel grind chamber, grinding elements and built-in air switch with chrome and brushed steel options.

Guarantee: 6 Year parts and service.


The complete InSinkErator guarantee is included in the Care & Use Booklet packed with each unit.

Batch feed operation



For those who prefer the on/off switch built right into the disposer cover, InSinkErator offers the cover control accessory. It's just right for efficient batch feed operation. (Not available in all markets)

Dimensions (mm)



Evolution 200			
A	344	D	234
B	185	E	168
C	64		

InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use; usage in commercial situations is not covered by warranty.

Specifications

Type of Feed	Continuous	Sound Technology	Anti-Vibration Mounting and Tailpipe
On/Off Control	Wall Switch or Built-In Air Switch		Quiet Sink Baffle
Motor	Single Phase		Multi-Layer Sound Insulation
Reversing	Auto-Reverse Grind System		Stainless Steel Strainer Basket and Plug
Time Rating	Intermittent	Grind Chamber Capacity	1180 ml
Lubrication	Permanently Lubricated Upper & Lower Bearings	Motor Protection	Manual Reset Overload
Shipping Weight (Approx.)	11.6 kg	Average Water Usage	Approximately 4.0 L per Person per Day
Unit Finish	Stainless Steel Light Gray TEN-1706	Average Electrical Usage	1/2 KWH per Month
Overall Height	344 mm	Drain Connection	1-1/2" (3.81 cm) Anti-Vibration (Hose Clamp)
Grind Technology	3-Stage Grind Technology Power Booster Circuit with Microprocessor Technology Included	Dishwasher Drain Connection	Yes

Volts/Hz	HP	RPM	Average Load
120V, 60 Hz	1.0	1725	10.2 A
220-240V, 50 Hz	.75	1425	380 W
220-240V, 60 Hz	.75	1725	370 W

InSinkErator Division
Suite 6, Building 6
Hatters Lane
Croxley Green Business Park
Watford HERTS WD18 8YH
United Kingdom
Sales Tel: (O) 1923 297 880
Service Tel: (O) 800 389 3715
www.insinkerator.co.uk
PN XXXXX REV A

InSinkErator Division
Emerson Electric Co.
4700 21st Street
Racine, WI 53406-5093 USA
Sales/Service Tel: 262-554-3652
www.insinkerator.com/worldmap.html



The Emerson logo is a trademark and a service mark of Emerson Electric Co. InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

©2009 InSinkErator, InSinkErator® is a division of Emerson Electric Co. All Rights Reserved.